

DYNAMAX

KOREA 

TECHNOLOGY



APPLICATIONS

BELLOWS
ISO 9001:2008

2016

BELLOWS
ISO 9001:2008

Innerbraid		
Number	Diameter, mm	Length, mm
D40x100	40	100
D40x150	40	150
D40x200	40	200
D40x230	40	230
D40x250	40	250
D40x280	40	280
D45x100	45,5	100
D45x150	45,5	150
D45x200	45,5	200
D45x230	45,5	230
D45x250	45,5	250
D45x260	45,5	260
D45x280	45,5	280
D50x100	51,3	100
D50x120	51,3	120
D50x150	51,3	150
D50x200	51,3	200
D50x220	51,3	220
D50x230	51,3	230
D50x250	51,3	250
D50x280	51,3	280
D50x300	51,3	300
D50x320	51,3	320
D50x350	51,3	350
D55x100	56	100
D55x120	56	120
D55x150	56	150
D55x200	56	200
D55x220	56	220
D55x230	56	230
D55x250	56	250
D55x280	56	280
D55x300	56	300
D55x320	56	320
D55x350	56	350
D60x100	61	100
D60x150	61	150
D60x200	61	200
D60x230	61	230
D60x250	61	250
D60x280	61	280
D64x100	65	100
D64x150	65	150
D64x200	65	200
D64x230	65	230
D64x250	65	250
D64x280	65	280
D65x150	65	150
D75x100	76	100
D75x150	76	150
D75x200	76	200
D75x250	76	250
D90x200	90	200
D100x150	100	150
D100x200	100	200
D110x300	110	300

Innerlock		
Number	Diameter, mm	Length, mm
D45x100R	45,5	100
D45x200R	45,5	200
D50x100R	51,3	100
D50x150R	51,3	150
D50x200R	51,3	200
D55x150R	56	150